


CMT-610 FLUSH WOOD GRAIN STEEL INSULATED DOOR

SERIES FEATURES

- 1 3/8" (34.9mm) - Thick CFC/HCFC-Free Polyurethane
- 13.45 Calculated R-Value
- .074 Calculated U-Value
- 26-Gauge Galvanized Steel
- Meets ASHRAE 90.1 Air Infiltration Requirements
- Full Thermal Break
- Available with Wind Load
- 17 Color Options
- 10-Year Rust & Delamination Warranty
- 1-Year Hardware
- 1-Year Spring

Cross Section



**1 3/8" (34.9mm)
Thick Sections**

AVAILABLE COLORS



Colors are not exact due to the differences in monitor and printer calibrations. For accurate color samples, contact Haas Door for a metal color selector. Trinar® colors carry a 35 year paint warranty.

MODEL FEATURES

- Extruded End Cap
- Flush wood grain embossment outside, V-groove pattern wood grain embossment inside
- Tongue and groove section joint

Exterior View



Interior View



600 SERIES LINKS

Click links for info.

[HOMEPAGE](#)

[BIM](#)

[BROCHURE](#)

[SPECS](#)

[GALLERY](#)

[SPECWIZARD](#)

[CAD](#)

[CATALOG](#)

Rev. 2.2 – August 2019